

GP[®] TITAN OVERTAPE

Rev: June 2019

Ground Gas Protection

JUTA GP[®] TITAN OVERTAPE - is an adhesive fleece backed tape designed for sealing joints of GP[®]TITANTECH waterproofing systems. The GP[®] TITAN OVERTAPE is single sided, with release film on one side. GP[®] TITAN OVERTAPE is designed to prevent the passage of water, water vapour, air and gas, for use in building construction with damp proof membranes, vapour control layers and ground gas barriers. It is specially formulated to act as a joint sealer for the GP[®] TITANBOND membrane to prevent concrete influx into the joint areas.

JUTA GP[®] TITAN OVERTAPE has excellent adhesion to all JUTA Gas Barriers, and a wide range of substrates. The flexible composition of the GP[®] TITAN OVERTAPE makes it highly conformable to irregular surfaces, and it is easy and accurate to use with little to no waste. JUTA GP[®] TITAN OVERTAPE has unrivalled levels of adhesion to the Gas Barriers and is designed to remain flexible throughout the service life.

JUTA GP [®] TITAN OVERTAPE			
Characteristic	Test Method	Unit	GP [®] TITAN OVERTAPE
Physical Properties			
Thickness	EN 1849-2	mm	1.00
Width	EN 1849-2	mm	100
Length	EN 1849-2	M	20
Packaging	4 rolls/Box		
Colour	Grey		
Adhesive	Pressure sensitive Butyl		
Mechanical Properties			
Peel Adhesion to GP [®] membranes	Modified PSTC	N/m	800
Application Temperature	-	°C	Above -5
Moisture vapour transmission rate	ISO 15106	g/m ² /24hr/mm	0.18

APPLICATION

Application temperature range is -5 to +40 °C. JUTA GP[®] TITAN OVERTAPE has a shelf life of 24 months when stored flat in original packaging in cool, dry conditions.

Prior to application, all surfaces should be clean, dry, and free from frost, grease and loose detritus materials. Apply direct from the reel onto the surface and press along the whole application length to achieve optimal adhesion. JUTA recommends the use of a silicon roller for optimal pressure application to taped joints.

COMPATABILITY


JUTA GP[®] TITAN OVERTAPE is compatible with our full range of Waterproof and Gas barriers, including:

- JUTA GP[®]1
- JUTA GP[®]2
- JUTA GP[®]H
- JUTA GP[®] TITANFLEX
- JUTA GP[®] TOP HATS AND PREFORMED CORNERS

ADDITIONAL INFORMATION

For additional information or assistance, please contact JUTA UK directly.

Contact us to find out more information.
info@juta.co.uk | 01772 754177 | JUTA.CO.UK
Melton Grove Works, Church Road, Lytham, FY8 5PL



JUTA



riba
product
selector